

## Optically Immersed 4.7 $\mu\text{m}$ LED in heatsink optimized housing

### LED47 Sr/Su/Cy

## TE cooled Optically Immersed 4.7 $\mu\text{m}$ LED


### LED47TO8TEC

| Peak wavelength   | μm  | 4.7±0.1                             |             | @22 °C  |
|-------------------|-----|-------------------------------------|-------------|---------|
|                   |     | LED47Sr/Su/Cy                       | LED47TO8TEC |         |
| Pulse power       | μW  | Drive current 1 A, 0.02 duty cycle  | 15÷18       | 13÷15   |
| Quasi-CW power    | μW  | Drive current 0.3 A, 0.5 duty cycle | 6.5÷8       | 5.5÷7   |
| CW power          | μW  | Drive current 0.2 A                 | 4.5÷5.5     | 3.8÷4.7 |
| Cut-off frequency | MHz | 50 <sup>1</sup>                     |             |         |

| Code           | Emission size, mm | Weight, g | Optical components                       | Far-field pattern FWHM, deg. | Optical axis deviation, deg. | Optical power deviation in lot, % | Operation conditions, °C | Lifetime, hrs |
|----------------|-------------------|-----------|------------------------------------------|------------------------------|------------------------------|-----------------------------------|--------------------------|---------------|
| LED47 Sr/Su/Cy | $\varnothing 3.2$ | ~0.4      | Si lens                                  | ~15                          | $\leq 5$                     | $\pm 25$                          | -60÷+85                  | >100 000      |
| LED47 TO8TEC   |                   | ~10       | Si lens and output sapphire window D=6mm |                              |                              |                                   |                          |               |



### Product view

LED47Cy






Pin assignment: red wire or long wire and red point on house - positive

LED47Sr



Pin assignment: red wire or long wire and red point on house - positive



Pin assignment  
LED47TO8TEC12

- 1 TEC negative;
- 3 TEC positive;
- 4 LED negative;
- 6 LED positive;
- 7, 9 thermosensor;
- 11  $\perp$  (House)

### Features

- Original growth of narrow gap semiconductor alloys onto n<sup>+</sup>-InAs substrate;
- Flip-chip design of LEDs;
- Optical coupling through the use of chalcogenide glasses and Si lenses with antireflection coating

- 3-fold increased LED output power;
- Beam collimation;
- Small on-off time (tenths of ns);
- Low power consumption ( $\leq 0.1\text{ W}$ )




Emission beam divergence is small and thus we recommend adjusting LED position regarding to the detector system before final evaluation/use of the devices. We recommend if possible using low duty cycle mode of operation with  $I < 0.5 \times I_{\text{max}}$  so that higher efficiency and long term stability of a LED are achieved. Data are valid for LED attached to a heatsink and thermostabilized at 22°C. Heatsink is essential for TEC operation!

### Notes

<sup>1</sup> - according to estimation

Product specifications are subject to change without prior notice due to improvements or other reasons. Updated 07.12.14

## Emission spectra



Power vs. temperature;  
 $I - V$  curveOutput power and drive  
current vs operation  
conditions

## Time dependence of the output power for several values of d.c. and currents (LED attached to a heatsink at room temperature).



“Safe” operation mode

“Maximum current” operation mode



Pulse operation (d.c.=0.06)



Quasi CW mode (d.c.=0.5)



CW mode (d.c.=1)



## Thermoelectric cooling module datasheet

| Mounted TEC | H, mm | $\Delta T_{\max}$ , K | $Q_{\max}$ , W | $I_{\max}$ , A | $U_{\max}$ , V | $R_{\theta}$ , K/W |
|-------------|-------|-----------------------|----------------|----------------|----------------|--------------------|
|-------------|-------|-----------------------|----------------|----------------|----------------|--------------------|

1MC06-024/1-15

2.6





70

1.86

1.0

2.78


1.07

Data for  $T_{\text{hot}} = 300$  K, from [www.tec-microsystems.com](http://www.tec-microsystems.com); [www.rmtitd.ru](http://www.rmtitd.ru)

## Type TB04-103

## Thermistor specification

| T, °C | R, kΩ  | T, °C | R, kΩ |
|-------|--------|-------|-------|
| -60   | 1134.5 | 15    | 12.44 |
| -55   | 762.4  | 20    | 10.00 |
| -50   | 521.6  | 25    | 8.09  |
| -45   | 362.8  | 25    | 8.09  |
| -40   | 256.3  | 30    | 6.60  |
| -35   | 183.8  | 35    | 5.41  |
| -30   | 133.6  | 40    | 4.47  |
| -25   | 98.3   | 45    | 3.71  |
| -20   | 73.3   | 50    | 3.10  |
| -15   | 55.2   | 55    | 2.61  |
| -10   | 42.1   | 60    | 2.20  |
| -5    | 32.4   | 65    | 1.87  |
| 0     | 25.2   | 70    | 1.59  |
| 5     | 19.7   | 75    | 1.37  |
| 10    | 15.6   | 80    | 1.18  |

Possible TEC  
heatsink view