

# MSA-300

## 5ns Photon Counter / Multiscaler

Ultra-fast accumulation

High repetition rate

No dead time between sweeps

No dead time between channels

Fast on-board discriminators

Input pulse width down to 800 ps



Time / channel down to 5 ns

Count rate up to 100 MHz

Up to 512 k points / curve

Software for Windows 95 / 98 / 2000 / NT

The MSA-300 is a fast multiscaler for photon counting, time-of-flight measurements or other fast particle detection applications. By using a 128 bit memory structure a dead-time-free accumulation of subsequent sweeps is achieved. This makes the MSA-300 exceptionally useful for a wide variety of high-repetition rate signal recording applications.



**Becker & Hickl GmbH**  
Nahmitzer Damm 30  
12277 Berlin  
Tel. 030 / 787 56 32 <http://www.becker-hickl.com>  
Fax. 030 / 787 57 34 email: [info@becker-hickl.com](mailto:info@becker-hickl.com)

US Representative:  
**Boston Electronics Corp**  
91 Boylston Street, Brookline,  
Massachusetts 02445 USA  
Tel: (800) 347 5445 or (617) 566 3821  
Fax: (617) 731 0935  
[www.boselec.com](http://www.boselec.com) [tcspc@boselec.com](mailto:tcspc@boselec.com)




# MSA-300

## Specification

Time per Channel	min. 5 ns
Count Rate	up to 100 MHz
No of Points / Curve	up to 512 k
Overall Recording Length	up to 2.62 ms
Accumulation (up to 256 events/point)	Hardware, no dead time between recording cycles
Accumulation (> 256 events/point)	Software
Count Input Impedance	50 $\Omega$
Count Input Amplitude	$\pm 20$ mV to $\pm 1$ V
Count Input Threshold	0 to $\pm 200$ mV, $\pm 8$ bit resolution
Min.Count Input Pulse Width	800 ps
Trigger Input Impedance	50 $\Omega$
Count and Trigger Input Connectors	MCX
Trigger Input Amplitude	$\pm 20$ mV to $\pm 1$ V
Trigger Input Threshold	0 to $\pm 1$ V, $\pm 8$ bit resolution
Min. Trigger Pulse Width	800 ps
Data Readout	subsequent data points are read by subsequent input instructions
Typical readout rate (Pentium 166 MHz)	1 $\mu$ s/point (C <sup>++</sup> , read 1 point and store into a data array)


## Luminescence Decay Measurements

The sample is excited by laser pulses and the luminescence signal is detected by a PMT in the photon counting mode. Due to the deep memory a time scale from ns to ms can be covered in one measurement.



## Time-of-Flight Measurements

Packages of ions are released by a pulsed source, sent through a drift tube and detected by an MCP. Due to the high accumulation speed of the MSA-300 very high repetition rates and short overall measurement times are achieved.



Accessories: PMTs, PMT detector heads with internal HV supply, preamplifiers, diode lasers, pulse generators for experiment control, step motor controllers. Please see individual data sheets.

Please visit our web site to download the manual, the device software and application notes.



**Becker & Hickl GmbH**  
Nahmitzer Damm 30  
12277 Berlin, Berlin  
Tel. +49 / 30 / 787 56 32 Fax +49 / 30 / 787 57 34  
<http://www.becker-hickl.com> [info@becker-hickl.com](mailto:info@becker-hickl.com)

**Boston Electronics Corporation**  
91 Boylston Street, Brookline.  
Massachusetts 02445 USA  
Tel: (800) 347 5445 or (617) 566 3821, Fax: (617) 731 0935  
[www.boselec.com](http://www.boselec.com) [tcspc@boselec.com](mailto:tcspc@boselec.com)

